



PRO
MILL

ProMILL-16

The ProMILL-16 is the results of an optimization study that involved the milling chamber, the nozzles and the classifier. This optimization bring FPS jet mill to lowest process gas consumption, to higher process performances and to easiest cleaning procedures.

All connections of components have been done in order to be in compliance with cGMPs to assure quick and easy assembling and disassembling operations.

It is available with different options:

- Special internal lining;
- CIP and SIP version;
- volumetric or gravimetric feeder;
- counter-pulse cyclone or fit with filtering sleeve;
- commands from manual to full automated PLC managed, compliant to GAMP and CFR21 Part11;
- ATEX certified;
- Explosion proof system;
- Cosmetic/pharma.

The ProMILL-16 may be easily integrated into dedicated FPS isolator system to allow the process of very high active or sterile products.

TECHNICAL DATA

Dimensions

16" milling chamber

Material

AISI316L / PTFE / Ceramic

Gaskets

PTFE – FEP / Viton-Silicone

Surface roughness

< 0.25µm – contact parts

< 0.80µm – non contact parts

Batch size

Minimum 20kg – Maximum 5000kg

Productivity

Minimum 10kg/h – Maximum 400kg/h

Yield

Up to 99,95% (depending on batch size)

Gas consumption

444 Nm³/h (@7barg supply)

761 Nm³/h (@12barg supply)

Working pressure

From 2 up to 12barg

Headquarters

F.P.S. Food and Pharma Systems S.r.l.

Via Vandelli,20 - 22100 Como (CO) - Italy

Tel. +39 031 543429 - Fax +39 031 540885

info@foodpharmasystems.com

Production and Test Facilities

F.P.S. Food and Pharma Systems S.r.l.

Via Romagnoli, 3 - 29017 Fiorenzuola d'Arda (PC) - Italy

Tel. +39 0523 984930 - Fax +39 0523 240218

Micronization systems | Containment systems